



PRODUCT INFORMATION

MUDD PRIME TIME

DESCRIPTION

For stabilising dusty or porous backgrounds prior to tiling.

MUDD PRIME TIME is a ready to use acrylic primer suitable for use on wall and floor surfaces prior to the application of Ceramic, Mosaic or Natural Stone Tiles in most interior and exterior situations including wet areas.

APPLICATION

Shake bottle before use. Apply 2 undiluted coats with a paintbrush on plaster, plasterboard, floorboards or screeds, or diluted with water 1:1 on plaster if using a ready mixed wall tile adhesive or on cement floors. Allow to dry for approx. 30 minutes between coats.

COVERAGE

1lt undiluted covers approx. 10m², on very porous backgrounds this may be less.

STORAGE & SHELF LIFE

Stored between 5°C and 30°C and protected from frost the shelf life of this product is 12 months.

USE OF PRODUCT

For further information on this or any MUDD product, please visit our website www.muddtiling.com or contact our helpline for advice.

Please refer to the Material Safety Data Sheet for further information on health and safety issues.

MUDD TECHNICAL ADVISORY SERVICE

For free expert guidance on the use of this product or any aspect of ceramic tiling telephone the **MUDD TECHNICAL ADVISORY SERVICE** on: **Tel:** 01782 591120 **Fax:** 01782 591121.



PRODUCT INFORMATION

Note: The customer must verify the suitability of any information, opinion, recommendation or advice ("Information") provided by the Company for the particular application for which any goods are intended to be used and the Company accepts no liability (whether in contract tort, or otherwise) whatsoever for any loss, damage, or expense arising from the misuse of any information it supplies nor for the use of any information in or for applications which are unsuitable or inappropriate. Building Adhesives Ltd operates a continuous research and development programme and reserves the right to alter or update information from time to time.